



**United States Patent** [19]  
**Wilson**

[11] **Patent Number:** **6,083,142**  
[45] **Date of Patent:** **Jul. 4, 2000**

- [54] **MOBILE, MODULAR CLIMBING TOWER**
- [75] Inventor: **Jeffrey D. Wilson**, Newcastle, Calif.
- [73] Assignee: **Extreme Engineering LLC**, Newcastle, Calif.
- [21] Appl. No.: **09/105,903**
- [22] Filed: **Jun. 26, 1998**

**Related U.S. Application Data**

- [60] Provisional application No. 60/073,016, Jan. 29, 1998.
- [51] **Int. Cl.**<sup>7</sup> ..... **A63B 9/00**
- [52] **U.S. Cl.** ..... **482/37; 482/35; 482/51;**  
472/136; 280/DIG. 8; 52/245
- [58] **Field of Search** ..... 482/35-37, 148;  
446/476; 472/136; 52/79.4, 245, 457, 578;  
250/423.1, DIG. 8

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

- 4,941,548 7/1990 Blanchard .
- 4,997,064 3/1991 Motte et al. .
- 5,092,587 3/1992 Ulner et al. .
- 5,125,877 6/1992 Brewer .
- 5,254,058 10/1993 Savigny .
- 5,256,116 10/1993 Robinson .
- 5,543,185 8/1996 Christensen .
- 5,593,368 1/1997 Checketts .
- 5,732,954 3/1998 Strickler et al. .... 482/37
- 5,941,041 8/1999 Robinson et al. .... 482/37

**FOREIGN PATENT DOCUMENTS**

- 81/01107 4/1981 WIPO ..... 482/35
- 91/08806 6/1991 WIPO ..... 482/37

**OTHER PUBLICATIONS**

FORM, Inc., 1964 catalog, S. Lyon, MI, p. 3, 482/35.  
Rubin, Diana. Scaling New Heights, The Washington Post Weekend, p. 59, May 16, 1997.

*Primary Examiner*—Richard J. Apley  
*Assistant Examiner*—Victor Hwang  
*Attorney, Agent, or Firm*—TownsendTownsend&Crew LLP; Mark D. Barrish, Esq.

[57] **ABSTRACT**

The invention provides improved climbing devices and structures for use in mobile and fixed climbing installations. The mobile climbing installation has a modular climbing tower pivotally mounted to a trailer to pivot between a road orientation and a climbing orientation. Modular climbing towers are generally assembled from panels having lateral curves by fastening upper and lower flanges of the panels together. The panels and flanges are integrally molded from fiberglass, and act as a monocoque structure. The climbing surface is on the radially outward portion of the partially or fully enclosed tower, thereby increasing the number of climbers that can safely be accommodated on a climbing surface of a given width. The invention also provides belaying devices for safely supporting a climber at the end of a flexible member such as a cable, rope, or the like. These belaying devices generally draw in the flexible member as the climber climbs. When the climber falls or completes the climbing route, the belay device supports the climber's weight, slowly and safely lowering the climber down to the ground. The exemplary auto-belay device makes use of a hydraulic piston mechanism to separate a pair of pulley assemblies. The flexible members runs back and forth between the pulley assemblies with a plurality of windings, so that the stroke of the hydraulic piston is significantly less than the height of the climbing structure.

**12 Claims, 14 Drawing Sheets**

